

AML: Matching SMS with HTTPS



Henning Schmidpott

Integrierte Leitstelle Freiburg · Breisgau-Hochschwarzwald (ILS)

Emergency Control Center Freiburg, Germany



Emergency call handling in Germany

- Two national emergency numbers:
 - 112: Fire and rescue, emergency medical services
 - 110: Police
- 16 federal states
 - 233 PSAPs handling 112 calls



Emergency control center Freiburg

- Population \approx 500.000
- 112 calls/year \approx 100.000
- Integrated in main fire station
- Own data center




AML endpoint Germany


- The national AML endpoint is provided by Freiburg Emergency Control Center since 2019.
- Redundancy endpoint in Berlin (passive).
- Over 230 PSAPs have access to AML endpoint.
- 60.000 HTTPS messages per day from Android devices.
- 80.000 SMS messages per day from Android and iOS devices.
- 3 messages per call (after 0s, 15s, 30s).



Integration in PSAP application




Integration in PSAP application



Statistics


Mobile emergency calls received by PSAP in Freiburg with AML location in %




AML in a privacy friendly way

- Delete all data on the endpoint after 1 hour
- Refuse not necessary data like IMSI, device model, ...
- device number is only stored as hash value in database

Location data flow



Location data process



Access to location data by API

- PSAP starts request to AML endpoint
- caller number as request parameter
- AML endpoint sends answer with location data for the requested caller number back to PSAP


=> Correct device number is significant!

Security issues with HTTPS?

risk	measure
Malicious code injection, SQL injection	<p>Check ELS data for compatibility. Refuse incompatible data. Examples:</p> <p>Characters in device_number may only include numbers and plus (e.g. +49171234567890)</p> <p>Characters in location_latitude may only include a dot(.) and numbers (e.g. 7.364758).</p>
DDoS attack	General practice like server redundancy, monitoring, use backbone protection from provider, isolate HTTPS-Server from SMS-Server
Fake/prank data	No problem unless the ELS data is associated to a real emergency call.

Matching HTTPS and SMS

- Use device_imei as key



Example dataset

HTTPS

location_time	device_number	location_latitude	location_longitude	location_accuracy	location_altitude	device_languages	device_imei	...
2022-06-28 15:00:00	0	49.654321	7.123456	29	129	de-DE,pl-PL	35249411446	

SMS

location_time	device_number	location_latitude	location_longitude	location_accuracy	location_altitude	device_languages	device_imei	...
2022-06-28 15:00:00	b81a97f74e8e15190c	49.654321	7.123456	29			35249411446	

HTTPS & SMS after merge

location_time	device_number	location_latitude	location_longitude	location_accuracy	location_altitude	device_languages	device_imei	...
2022-06-28 15:00:00	b81a97f74e8e15190c	49.654321	7.123456	29	129	de-DE,pl-PL	35249411446	

Roaming

- HTTPS is a easy solution to provide AML for roaming caller.
- Data volume is very small so the costs are not significant.
- About 5% of all HTTPS datasets we receive are from roaming caller.